

## Automatska rampa 4 i 6 m, Italija

- Made of galvanized steel and painted with epoxy powder
- Robust materials unchanging over time
- For bars up to 4m and 6m
- *Unique version left and right*
- Magnetic limit switches for opening and closing
- Grease lubrication
- Intrinsically safe Balancing system of the bar - **PATENTED**
- Easy installation
- Motor SLS system inside - **PATENTED**
- *Intensiv use*
- Easy manual release
- Available color: Yellow RAL 1023 - other colors available by quantities

TECHNICAL DATA	GR220V
POWER SUPPLY (V 220ac 50/60Hz)	220
POWER ABSORBED (W)	180
CURRENT ABSORBED (A)	0,8
CAPACITOR (µF)	8,0
OPENING TIME (sec)	7,0
MAX. BAR LENGHT (m)	4,0
SPEED (rpm)	2800
WORKING TEMP. (°C)	-25 +60
THERMAL PROTECTION (°C)	150
PREOTECTION LEVEL (IP)	40
WORKING CYCLES (%) / DAYLY OPERATIONS	80 / > 4000
MOVUMENT	ELECTRO-MECHANICAL PISTON
RELEASE	MANUAL WITH KEY
DIMENSIONS AND WEIGHT	324x282x1130mm / 44,0 kg

